

PRZEDSIĘBIORSTWO USŁUGOWO REMONTOWE
REMODEX
ZAKŁAD BADAŃ I WDROŻEŃ PRZEMYSŁU MEBLARSKIEGO
Spółka z o.o.

Gruszczyn, ul. Leśna 12
62-006 Kobylnica

e-mail: biuro@remodex.com.pl
KRS 0000099068

tel. kom. 601 391 825

SIGN: BW/PB/84/2025

DATE: 2025-05-28

Order from: 2025-04-08

TEST REPORT No: 76/25/W

Safety requirements, strength and durability

1. *Name and type of article -*

Swivel chair CUTLER GF

2. *CLIENT -*

STEMA P.S.A.
ul. Towarowa 22A
58-100 ŚWIDNICA

3. *Documents identifying article -*

order + technical records.

This article was tested in accordance
with the test procedures described in:

PN-EN 1335-2:2019-03
PN-EN 1728:2012/AC:2013
PN-EN 1022:2024-04

TEST RESULTS:

POSITIVE

Test operator



.....
/M Sc. (Eng.) Piotr Błaszczak

PREZES ZARZĄDU


mgr inż. Piotr Błaszczak

TEST REPORT contain 3 pages

The test results are only valid for the article tested.

This TEST REPORT shall not be reproduced except in full, without the written approval of the laboratory.

SWIVEL CHAIR

The name, symbol and the type of article: **Swivel chair CUTLER GF**

SAFETY REQUIREMENTS:

| point PN-EN | Test description | Requirement | Test results |
|-------------|--|---|----------------|
| 4.1 | the edges of the seat, back rest, armrests | rounded with minimum 2 mm radius | positive |
| | the edges of handles | rounded or chamfered | positive |
| | other edges | free from burrs rounded or chamfered | positive |
| | the ends and accessible hollow components | closed or capped | not applicable |
| | movable and adjustable parts | they do not cause injury | positive |
| | handling adjusting devices | from sitting position | positive |
| | connection of load-bearing parts | they do not loosen | positive |
| 4.2.1 | shear and squeeze points under influence of powered mechanisms | inadmissible | positive |
| 4.2.2 | shear and squeeze points during use | inadmissible | positive |

STABILITY:

| No | Test description | Loading | Test results |
|----|---|---|----------------|
| 1 | Forward overturning | vertical force F_1 600 N horizontal force F_2 20 N | pass |
| 2 | Forward overturning for chair with footrest | vertical force F_1 1100 N horizontal force F_2 20 N | not applicable |
| 3 | Front edge overturning | vertical force F_1 300 N | pass |
| 4 | Sideways overturning for chairs with arm rests | vertical force F_1 250 N vertical force F_2 350 N horizontal force F_3 20 N | pass |
| 5 | Sideways overturning for chairs without arm rests | vertical force F_1 600 N horizontal force F_2 20 N | pass |
| 6 | Rearwards overturning for chairs with blocking the back rest position | vertical force F_1 600 N horizontal force F_2 137 N | pass |
| 7 | Rearwards overturning of chairs with back rest inclination | number of discs: 13 (130 kg) | pass |

LABORATORIUM

SIGNED: 

SWIVEL CHAIR

The name, symbol and the type of article: **Swivel chair CUTLER GF**

STRENGTH and DURABILITY

| No | Part of furniture | Loading | cycles | Re-quire-ment | Test results | |
|---------|---------------------------------|---|------------------------|-----------------|----------------------|------|
| 1 | static load - seat - back | vertical force 1600 N horizontal force 560 N | 10 | without defects | pass | |
| 2 | seat front edge static load | vertical force 1600 N | 10 | | pass | |
| 3 | foot rest static load | vertical force 1300 N | 10 | | not applicable | |
| 4 | Seat and back durability | point A | vertical force 1500 N | | 120000 | pass |
| | | point C | vertical force 1200 N | | 80000 | pass |
| | | point B | horizontal force 320 N | | | |
| | | point J | vertical force 1200 N | | 20000 | pass |
| | | point E | horizontal force 320 N | | | |
| point F | vertical force 1200 N | 20000 | pass | | | |
| point H | horizontal force 320 N | | | | | |
| 5 | arms | force 400 N, angel 10° to the vertical | 60000 | pass | | |
| | | vertical force 750 N | 5 | pass | | |
| | | vertical force 900 N | 5 | pass | | |
| 6*/ | resistance of rolling castors | force minimum 12 N | --- | --- | force – 20 N pass | |

*/- castors type H, self-braking, Ø 60 mm

Attention: the admissible maximum loading of seat - **150 kg**.

LABORATORIUM

SIGNED: .....